


REV	DESCRIPTION	ECN#	DWN	APVD	DATE
A	ISSUED ENGINEERING DRAWING	1646	KJM	KRW	2/0/09
	ADDED WEIGHT BOX		PMK		03NOV14



Ø34.9
[1.38]
MAX OPTIONAL
FOR MACHINING
AND/OR
ALIGNMENT
PURPOSES

Ø10.7
[0.42]
8X
EQUALLY SPACED

Ø155.58
[6.125]
B.C.

C084708
180-10mm

JACKING SCREW
3/8-16 UNC - 2B
2X EQUALLY SPACED

19.1
[0.75]

Ø109.9
[4.33]

352.4
[13.875]

Ø333.38
[13.125]
B.C.


M16x2 - 6H
10X

2.29
[0.090]

WEIGHT: lb (kg)
31.4 (14.2)

BOLT TORQUE
210 FT-LBS

- NOTES:
1. REMOVE ANY/ALL SHARP EDGES AND BURRS.
 2. ALL THRU HOLES TO BE FREE OF ALL BURRS AND/OR OBSTRUCTIONS.
 3. IDENTIFY PART NUMBER BY EITHER STAMPING OR ETCHING.
 4. BREAK ALL CORNERS R1.0 [0.04] MAX.



TYPICAL ADAPTER DISC MOUNTING
OF SC2160 SERIES DRIVE SHAFTS

CLARKE
Fire Protection Products, Inc.

NAME: ADAPTER DISC for SC2160 DRIVESHAFT

MATERIAL	PART NO.	REV.
Steel, Mild	C084708-W	A
SCALE	UNITS	PAGE
NTS	MM [INCH]	1 OF 1