



NOTE

- 1) VERIFY HEATER VOLTAGE PRIOR TO CONNECTING TO POWER SOURCE.
- 2) POWER SOURCE AC SUPPLY 230VAC +5%/-10%

B	REMOVED THIRD HEATER FROM SCHEMATIC	KFB	ASC	04MAY16
A	ISSUED ENGINEERING DRAWING	ASC	KJK	29OCT10
SYM	REVISION	ENGR	APVD	DATE
THIS DRAWING AND THE INFORMATION HEREON ARE OUR PROPERTY AND MAY BE USED BY OTHERS ONLY AS AUTHORIZED BY US. UNPUBLISHED--ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	DWN	ACRISTOFARD		
	DATE	29OCT10		
	ENGR	KKUNKLER		
	CHK			
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: MM IN DECIMAL .X ±1.5 ±0.06 .XX ±0.8 ±0.03 .XXX ±0.25 ±0.01 FRACTIONAL ±1/32 ANGULAR ±.5°	NAME		CLARKE <i>Fire Protection Products, Inc.</i>	
	WIRING DIAGRAM LC2A-LP HEATER 240VAC		SIZE	REV
USAGE: 1000 SERIES	INSP	SERIES CODE	SCALE	UNITS
	Y	MP	NONE	NONE
				SHEET OF 1 1